

## The Organ in Holy Trinity Church, Wavertree

Specification of the organ installed by J.W.Walker in 1972 and improved by David Wells Organ Builders with the addition of a Tuba stop from St. Agnes, Ullet Road.

### Great

1.	Contra Salicional	16'	from 13
2.	Open Diapason	8'	
3.	Stopped Diapason	8'	
4.	Salicional	8'	from 13
5.	Principal	4'	
6.	Stopped flute	4'	from 3
7.	Twelfth	2 $\frac{2}{3}$ '	from 5
8.	Fifteenth	2'	from 5
9.	Mixture	15.19.22	
10.	Trumpet	8'	
11.	TUBA	8'	

i) Swell to Great

### Swell

12.	Gedact	8'	
13.	Salicional	8'	
14.	Flute	4'	from 12
15.	Salicet	4'	from 13
16.	Nazard	2 $\frac{2}{3}$ '	from 12
17.	Flautino	2'	from 12
18.	Larigot	1 $\frac{1}{2}$ '	from 19
19.	Mixture	22.26.29	
20.	Double Trumpet	16'	
21.	Trumpet	8'	from 20
22.	Clarion	4'	from 20
23.	TUBA	8'	

ii) Octave

iii) Sub-octave

iv) Unison off

Tremulant

### Pedal

24.	Open Wood	16'	
25.	Bourdon	16'	
26.	Principal	8'	from 24
27.	Bass Flute	8	from 25
28.	Fifteenth	4'	from 24
29.	Octave Flute	4'	from 25
30.	Trombone	16'	from 20
31.	Trumpet	8'	from 10

v) Swell to Pedal

vi) Great to Pedal

Great and Pedal Combinations Coupled

Couplers i), v), vi) are reversible with thumb and toe pistons.

Six thumb pistons to Great; Six thumb pistons to Swell (duplicate toe pistons which can also be Generals):

Six toe pistons to Pedal: Six General thumb pistons: General Cancel thumb piston.

Eight channel capture system.